

NOT FOR SALE IN CALIFORNIA.

DIS-SOLV Paint Stripper is a powerful clinging gel that quickly blisters lacquers, enamels, shellacs, and acrylics without attacking substrates such as wood, metal, masonry, stone or ceramics. Blistered paint can be scraped off or flushed away with water.

DIRECTIONS:

SHAKE VIGOROUSLY BEFORE EACH USE. Clean off dirt, grease or heavy oil. Make certain surface is dry. To avoid possible skin contact, do not stand downwind of spray or mist during application. Hold can 8 to 10 inches from surface. Apply a heavy, even coat to entire surface. Allow product to remain on surface for several minutes, even after blistering action has occurred. Remove residue with a scraper, putty knife, cloth or a strong water spray. If necessary, repeat application after surface is dry. Clean valve by turning can upside down and applying short bursts.

See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY:
1-866-836-8855. CONTAINS NO OZONE
DEPLETING CHEMICALS!
MADE IN CANADA

To Reorder:

WECHEM, INC.

5734 Susitna Dr Harahan, LA 70123
504.733.1152 · 800.426.0512
fax 504.733.2218 · www.wechem.com



Engineered Chemistries
SUPERIOR SOLUTIONS

DIS-SOLV **GASKET & PAINT STRIPPER**

CLINGING GEL
with
FAST BLISTERING ACTION

SCRAPE OFF
or
WATER FLUSH OFF

WARNING

FLAMMABLE.

MAY CAUSE EYE IRRITATION.

CONTENTS UNDER PRESSURE.

READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.

NET WT. 18 OZ (1 LB 2 OZ) 510 g

2/15



DANGER

Extremely flammable aerosol. Harmful if swallowed. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No Smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 120°F (49°C). Dispose of content/container in accordance with local /regional/national/international regulations.

FIRST AID

IF SWALLOWED: Call a poison center/doctor if you feel unwell. Rinse mouth. **If exposed:** Call a poison center/doctor. **IF ON SKIN:** Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Call a physician or Poison Control Center immediately. Get medical attention if irritation develops or persists. **IF IN EYES:** Get medical attention if irritation develops or persists. Call a physician or Poison Control Center immediately. **IF INHALED:** Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately.

CONTAINS: Methylene Chloride (75-09-2), Propane (74-98-6), Butane (106-97-8), Methanol (67-56-1), Toluene (108-88-3), and Propylene Oxide (75-56-9).

WARNING: Can be harmful or fatal at high concentrations. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Protect surrounding objects from overspray. Solvent will attack plastics, asphalt, tile and many synthetic materials. Do not allow scraping or washings to contact food or live vegetation. Use of chemical resistant gloves is recommended, especially if skin is subject to allergy or rash. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.