

FOR INDUSTRIAL USE - NOT FOR RETAIL SALE

FOR USE IN THE MANUFACTURING PROCESS ONLY.

READ ENTIRE LABEL CAREFULLY BEFORE USING PRODUCT.

Contains Dimethylpolysiloxane (Poly Dimethylsiloxane; Dimethyl Silicone Fluid) with viscosity over 300 centistokes is listed in FDA regulations as a lubricant with incidental food contact.

- Contains **NO Chlorinated Solvents**
- **NO CFC's • NON-HEXANE • NON-STAINING**
- **DRIES FAST • SAFE ON PLASTIC**
- FOOD GRADE SILICONE IS HEAT STABLE FROM -40°F to over 392°F**

USES: By following the provisions of the FDA regulations in 21 CFR, Part 178.3570 and 178.3530, this Silicone Spray with incidental food contact may be safely used on machinery used for producing, manufacturing, packing, processing, preparing, treating, packaging, transporting, or holding food.

This Silicone Spray may be used on food-processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is exposure of the lubricated part to food. The amount used must be the minimum required to accomplish the desired technical effect on the equipment, and the addition to food of the Dimethylpolysiloxane cannot exceed 1 ppm.

Use as a lubricant, release agent, water repellent, protective coating, and polish. The dry Silicone film is non-flammable, colorless, odorless, nonstaining, waxless, and heat-stable; unaffected by temperatures ranging from -40°C (-40°F) to over 200°C (392°F).

Use on such equipment as ovens, freezers, conveyors, belts and chutes. Proper use of Silicone Spray minimizes clean-up time, speeds equipment disassembly, stops sticking and binding, protects equipment, and increases production.

Use on cool ovens ONLY. Avoid spraying pilot light. Ends "poly build-up" on surfaces such as mandrels, transfers chutes, and guide rails on paper carton machines. Coats hot or cold sealing bars on heat-sealing equipment. Prevents waxes, films, adhesives, and glues from collecting and jamming high speed equipment. Keeps waxed paper and plastic film from sticking and tearing. Eliminates pile-up, browning and ink smear. Assures a clean package every time.

DIRECTIONS: Thoroughly clean surfaces to be treated. Use steel wool on metals, and wipe with a good, compliant cleaning solvent if necessary. Clean rubber and plastic surfaces with detergent solution, rinse, and dry thoroughly. Spray a thin, light Silicone film; avoid over spraying. Remove excess with a clean cloth. Renew when necessary. **ATTENTION:** Do not allow spray, mist or coating to cover floors; they may become slippery, especially when wet.



**Engineered Chemistries
SUPERIOR SOLUTIONS**

GLIDE™
**DRY
SILICONE
SPRAY**

**FOOD GRADE FOR THE
FOOD PACKAGING AND
PROCESSING INDUSTRY**

**DANGER:
HARMFUL OR FATAL IF SWALLOWED
FLAMMABLE**
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL

NET WT. 11 OZ (312 g)

REV 12/14



GLIDE Dry Silicone Spray

DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters the airways. Keep away from heat/sparks/ open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

CONTAINS: Butane (106-97-8), Propane (74-98-6), Odorless Mineral Spirits (64741-65-7), and Polydimethylsiloxane (63148-62-9).

Caution: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

See Safety Data Sheet for complete safety information. **24 HOUR MEDICAL EMERGENCY: 1-866-836-8855. CONTAINS NO OZONE DEPLETING CHEMICALS!**



To Reorder:
WECHEM, INC.

5734 Susitna Drive, Harahan, LA 70123
(504) 733-1152 · FAX (504) 733-2218
800-426-0512 · www.wechem.com



7 38435 20523 2