

DESCRIPTION

TF LUBE is a chemically inert, non-oily, non-staining lubricant and release agent that is clean and dry during use. The extremely slick nature of this waxy fluorocarbon will not dissolve away from surfaces and will not melt below 500°F. It repels oil and water, will not attract or hold dust or dirt, and will not become gummy. It is suitable for use as a release agent for rubber, epoxy, phenolic, polyester and other resins.

AN EXCELLENT DRY COATING LUBRICANT FOR SAW BLADES, ROUTER BITS, DRILL BITS, SHAPERS, PLANERS, TABLE TOPS, ETC. Reduces friction, inhibits resin build-up and prolongs tool life.

DIRECTIONS:

Shake well before using. Spray a light thin coat from a distance of approximately 6 inches. Paintable and contains no silicone or oil. Will not affect wood finish.

CAUTIONS: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Use with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.** Warning: This product contains a chemical(s) known to the state of California to cause cancer and birth defects or other reproductive harm.

To Reorder:
WECHEM, INC.

5734 Susitna Dr. Harahan, LA 70123
504.733.1152 · 800.426.0512
fax 504.733.2218 · www.wechem.com



Engineered Chemistries
SUPERIOR SOLUTIONS

TF LUBE™

DRY LUBRICANT & RELEASE AGENT with PTFE

PAINTABLE PROLONGS TOOL LIFE REDUCES FRICTION STOPS STICKING

**DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
MAY CAUSE EYE IRRITATION.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.**

NET WT. 12 OZ. (340 Grams)

REV 5/15



TF LUBE™

DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C (120°F). Dispose of contents/container in accordance with local/regional/national/international regulations.

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

CONTAINS: Butane (106-97-8), Propane (74-98-6), Solvent Naphtha (petroleum), Light Aliphatic (64742-89-8), Acetone (67-64-1), n-Heptane (142-82-5), Ethyl Alcohol (64-17-5), Cyclohexane (110-82-7), Toluene (108-88-3), and n-Hexane (110-54-3).

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY: 1-866-836-8855. CONTAINS NO OZONE DEPLETING CHEMICALS! KEEP OUT OF REACH OF CHILDREN.