

## PENETRATING HIGH TACK FORMULA

A high tack, clear, lubricating gel which provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Deposits a fine polytetrafluoroethylene and gel lubricant mixture deep inside working parts. Resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film. Safe on most plastics.

### USE ON:

Gears, sprockets, hinges, chains, cable, wire rope, slides, valves, pistons, rings, seals, bearings, sleeves, cams and bushings.

### USED BY:

Machine shops, light and heavy manufacturing, HVAC, plumbing and other trades. Automotive and virtually all maintenance or repair operations.

### DIRECTIONS: SHAKE WELL BEFORE USING

Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12 to 14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.

To Reorder: WECEM, INC.

5734 Susitna Dr. Harahan, LA 70123

504.733.1152 · 800.426.0512

fax 504.733.2218 · [www.wechem.com](http://www.wechem.com)



Engineered Chemistries  
SUPERIOR SOLUTIONS

# Ultra Gel Lube™

Penetrating Gel Lubricant With PTFE

• High Tack

• Safe on Most Plastic

• Effective From -30°F to +500°F

## DANGER:

**EXTREMELY FLAMMABLE**  
**HARMFUL OR FATAL IF SWALLOWED**  
**MAY CAUSE EYE AND SKIN IRRITATION**  
**CONTENTS UNDER PRESSURE**  
**SEE OTHER CAUTIONS ON BACK PANEL**

**NET WT. 12 OZ (340 Grams)**



### ULTRA GEL LUBE™

**DANGER:** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Stored locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

**IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF SWALLOWED:** Immediately call a poison center/doctor. Do NOT induce vomiting.

Contains: Acetone (67-64-1), Petroleum distillates, hydrotreated light (64742-47-8), Aliphatic Petroleum Solvent (64742-89-8), Carbon Dioxide (124-38-9), n-Heptane (142-82-5), Cyclohexane (110-82-7), Toluene (108-88-3), and n-Hexane (110-54-3).

**CAUTION: Intentional misuse by concentrating and inhaling the product can be harmful or fatal.**  
**KEEP OUT OF REACH OF CHILDREN.**

See Safety Data Sheet for complete safety information.

**24 HOUR MEDICAL EMERGENCY:**  
1-866-836-8855. **CONTAINS NO OZONE DEPLETING CHEMICALS!**