

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 1 of 13

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr
Harahan, LA 70123

Contact: Ligia M. Hernandez
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Identifier: Dis Solv
SDS Number: A65H
Product Code: A65
Revision Date: 1/23/2018
Product Use: Gasket and Paint Stripper

Emergency Telephone Number:
1-800-535-5053

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
Health, Carcinogenicity, 1
Health, Reproductive toxicity, 1
Health, Specific target organ toxicity - Repeated exposure, 2
Environmental, Hazards to the aquatic environment - Acute, 3
Environmental, Hazards to the aquatic environment - Chronic, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
H350 - May cause cancer
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

GHS Precautionary Statements:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P260 - Do not breathe gas.
P264 - Wash thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 2 of 13

P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P307+311 - IF exposed: Call a POISON CENTER or doctor/physician.
 P321 - Specific treatment (see this label).
 P330 - Rinse mouth.
 P405 - Store locked up.
 P410+412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Ingestion, Inhalation, skin absorption, eye
Inhalation: May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin Contact: No adverse effects due to skin contact are expected.
Eye Contact: Direct contact with eyes may cause temporary irritation.
Ingestion: Expected to be a low ingestion hazard.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
75-09-2	60-80%	Methylene chloride
75-28-5	2.5-10%	Isobutane
67-56-1	2.5-10%	Methanol
74-98-6	2.5-10%	Propane
108-88-3	2.5-10%	Toluene

Other components below reportable levels 1-2.5%

4 FIRST AID MEASURES

Inhalation: Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Skin Contact: Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Call a physician or Poison Control Center immediately. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Eye Contact: Get medical attention if irritation develops or persists. Call a physician or Poison Control Center immediately.
Ingestion: Have victim rinse mouth thoroughly with water. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Get medical attention immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

Most important symptoms/effects are prolonged exposure may cause chronic effects.

Dizziness. Nausea. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5 FIRE FIGHTING MEASURES

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 3 of 13

Flammability:	Extremely Flammable
Flash Point:	15.0 °F (-9.4 °C) estimated
Burning Rate:	ND
Autoignition Temp:	ND
LEL:	ND
UEL:	ND

Suitable extinguishing media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

6

ACCIDENTAL RELEASE MEASURES

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7

HANDLING AND STORAGE**Handling Precautions:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Avoid release to the environment. Observe good industrial hygiene practices.

Storage Requirements:

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 5 of 13

Isobutane cas#:(75-28-5) [2.5-10%]

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Cardiac sensitization

TWA 800 ppm USA. NIOSH Recommended Exposure Limits
1,900 mg/m³

Also see specific listing for n-Butane.

Methanol cas#:(67-56-1) [2.5-10%]

Components with workplace control parameters

TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV)
Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption

STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV)
Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption

TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
260 mg/m³ 1910.1000
Skin notation

STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
325 mg/m³ 1910.1000
Skin notation

TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
260 mg/m³ Limits for Air Contaminants
The value in mg/m³ is approximate.

TWA 200 ppm USA. NIOSH Recommended Exposure Limits
260 mg/m³
Potential for dermal absorption

ST 250 ppm USA. NIOSH Recommended Exposure Limits
325 mg/m³
Potential for dermal absorption

Propane cas#:(74-98-6) [2.5-10%]

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values
(TLV)
Central Nervous System impairment
Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits
1,800 mg/m³ (OSHA) - Table Z-1 Limits for Air

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 6 of 13

ContaminantsThe value in mg/m³ is approximate.

TWA	1,000 ppm 1,800 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
-----	--------------------------------------	--

TWA	1,000 ppm 1,800 mg/m ³	USA. NIOSH Recommended Exposure Limits
-----	--------------------------------------	---

Toluene cas#:(108-88-3) [2.5-10%]

Components with workplace control parameters

TWA	100 ppm 375 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
-----	----------------------------------	--

STEL	150 ppm 560 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
------	----------------------------------	--

TWA	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
-----	---------	--

Z37.12- 1967

CEIL	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
------	---------	--

Z37.12- 1967

Peak	500 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
------	---------	--

Z37.12- 1967

TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
-----	--------	--

Visual impairment

Female reproductive

Pregnancy loss

2010 Adoption

Substances for which there is a Biological Exposure Index or Indices
(see BEI section)

Not classifiable as a human carcinogen

TWA	100 ppm 375 mg/m ³	USA. NIOSH Recommended Exposure Limits
-----	----------------------------------	---

ST	150 ppm 560 mg/m ³	USA. NIOSH Recommended Exposure Limits
----	----------------------------------	---

Methylene chloride cas#:(75-09-2) [60-80%]

Components with workplace control parameters

Potential Occupational Carcinogen

See Appendix A

TWA	50 ppm	USA. ACGIH Threshold Limit Values
-----	--------	-----------------------------------

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 8 of 13

TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
260 mg/m3 1910.1000

Skin notation

STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
325 mg/m3 1910.1000

Skin notation

TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
260 mg/m3 Limits for Air Contaminants
The value in mg/m3 is approximate.

TWA 200 ppm USA. NIOSH Recommended Exposure Limits
260 mg/m3
Potential for dermal absorption

ST 250 ppm USA. NIOSH Recommended Exposure Limits
325 mg/m3
Potential for dermal absorption

Propane cas#:(74-98-6) [2.5-10%]

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values
(TLV)
Central Nervous System impairment
Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits
1,800 mg/m3 (OSHA) - Table Z-1 Limits for Air
Contaminants
The value in mg/m3 is approximate.

TWA 1,000 ppm USA. OSHA - TABLE Z-1 Limits for
1,800 mg/m3 Air Contaminants - 1910.1000

TWA 1,000 ppm USA. NIOSH Recommended
1,800 mg/m3 Exposure Limits

Toluene cas#:(108-88-3) [2.5-10%]

Components with workplace control parameters

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for
375 mg/m3 Air Contaminants - 1910.1000

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for
560 mg/m3 Air Contaminants - 1910.1000

TWA 200 ppm USA. Occupational Exposure Limits
(OSHA) - Table Z2

Z37.12- 1967

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 9 of 13

CEIL 300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2
Z37.12- 1967

Peak 500 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2
Z37.12- 1967

TWA 20 ppm USA. ACGIH Threshold Limit Values (TLV)

Visual impairment
Female reproductive
Pregnancy loss
2010 Adoption
Substances for which there is a Biological Exposure Index or Indices (see BEI section)
Not classifiable as a human carcinogen

TWA 100 ppm USA. NIOSH Recommended Exposure Limits
375 mg/m3

ST 150 ppm USA. NIOSH Recommended Exposure Limits
560 mg/m3

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Compressed liquefied gas.	Odor:	Not available
Physical State:	Liquid	Solubility:	Not available
Spec Grav./Density:	0.16 g/cm3 estimated	Flash Point:	15.0 °F (-9.4 °C) estimated
Boiling Point:	-16.28 °F (-26.82 °C) estimated	Vapor Density:	Not available
Vapor Pressure:	Not available	VOC:	98.4%wt estimated
pH:	Not available	Auto-Ignition Temp:	1007.48 °F (541.93 °C) estimated
		UFL/LFL:	17.6% / 10.5% estimated

10

STABILITY AND REACTIVITY

Chemical Stability:	Stable and non-reactive under normal conditions of use, storage and transport.
Conditions to Avoid:	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Materials to Avoid:	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous Decomposition:	No hazardous decomposition products are known.
Hazardous Polymerization:	Does not occur.

11

TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 10 of 13

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dizziness. Nausea.

Data summary for the components are as follows:

Isobutane (75-28-5)

Inhalation LC50 1237 mg/l, 120 minutes (Mouse)
LC50 52%, 120 minutes (Mouse)
LC50 1355 mg/l (Rat)

Methanol (67-56-1)

Inhalation LC50 85.41 mg/l, 4.5 hrs (Cat)
LC50 43.68 mg/l, 6 hrs (Cat)
LC50 79.43 mg/l, 134 mins, (Mouse)
LC50 >115.9 mg/l, 4 hrs (Rat)
LC50 82.1 mg/l, 6 hrs (Rat)
Oral LD50 6000 mg/kg (Monkey)
LD50 1187-2769 mg/kg (Rat)
LD50 >5000 mg/kg (Pig)
Other LD50 6000 mg/kg (mouse)

Methylene chloride (75-09-2)

Dermal LD50 >2000 mg/kg, Days (Rat)
Inhalation LC50 49 mg/l, 7 hrs (Mouse)
Oral LD50 >3000 mg/kg (Rat)

Propane (74-98-6)

Inhalation LC50 1237 mg/l, 120 mins. (Mouse)
LC50 52%, 120 mins. (Mouse)
LC50 1355 mg/l (Rat)
LC50 658 mg/l, 4 h (Rat)

Toluene (108-88-3)

Dermal LD50 >5000 mg/kg, 24 hrs (Rabbit)
Inhalation LC50 6405-7436 ppm, 6 hrs (Mouse)
LC50 5320 ppm, 8 hrs (Mouse)
LC50 5879-6281 ppm, 6 hrs (Rat)
LC50 12.5-28.8 mg/l 4 hrs (Rat)
Oral LD50 5000 mg/kg (Rat)

Product not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization is not available.

Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (Rash).

May cause genetic defects.

May cause Cancer.

May damage fertility of the unborn child.

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 11 of 13

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

This product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Harmful to aquatic life with long lasting effects.

Ecotoxicity:

Data summary for the components are as follows:

Methanol (67-56-1)

Aquatic

Crustacea EC50 >10000 mg/l, 48 hrs water flea (Daphnia magna)
 Fish LC50 >100 mg/l, 96 hrs Fathead minnow (Pimephales promelas)

Methylene chloride (75-09-2)

Aquatic

Algae IC50 500.0001 mg/L, 72 hrs (Algae)
 Crustacea EC50 1689.5 mg/L, 48 hrs (Daphnia)
 EC50 1250 mg/l, 48 hrs water flea (Daphnia magna)
 Fish LC50 140.8-277.8 mg/l, 96 hours Fathead minnow (Pimephales promelas)

Toluene (108-88-3)

Aquatic

Algae IC50 433.0001 mg/L, 72 hrs (Algae)
 Crustacea EC50 7.645 mg/L, 48 hrs (Daphnia)
 EC50 5.46-9.83 mg/l, 48 hrs water flea (Daphnia magna)
 Fish LC50 8.11 mg/l, 96 hrs, Coho salmon, silver salmon (Oncorhynchus kisutch)

Partition coefficient n-octanol / water (log Kow)

Isobutane 2.76
 Methanol -0.77
 Methylene Chloride 1.25
 Propane 2.36
 Toluene 2.73

No data on the mobility in soil.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 12 of 13

its container must be disposed of in a safe manner (see: Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14	TRANSPORT INFORMATION
----	------------------------------

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1 (PGIII)
Label(s)	2.1,6.1
Packing group	Not applicable
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity until 12/31/2020, the "Consumer Commodity-ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking on both and may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1 (PGIII)
Label(s)	2.1,6.1
Packing group	Not applicable
Environmental hazards	No
ERG Code	10P
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed
Aircraft	
Cargo aircraft only	Allowed
Packaging exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1 (PGIII)
Label(s)	2.1 + 6.1
Packing group	Not applicable
Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	NOT a LTD QTY

Dis Solv

SDS Number: A65H

Revision Date: 1/23/2018

Page 13 of 13

Transport in bulk according to AnnexII of MARPOL 73/78 and the IBC Code Not applicable.

15	REGULATORY INFORMATION
-----------	-------------------------------

Component (CAS#) [%] - CODES

RQ(1000LBS), Methylene chloride (75-09-2) [60-80%] CERCLA, GADSL, HAP, MASS, NJHS, NRC, OSHAWAC, PA, PRIPOL, PROP65, SARA313, TOXICPOL, TOXICRCRA, TSCA, TXAIR, TXHWL

Isobutane (75-28-5) [2.5-10%] MASS, PA, TSCA

RQ(5000LBS), Methanol (67-56-1) [2.5-10%] CERCLA, GADSL, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

Propane (74-98-6) [2.5-10%] MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

RQ(1000LBS), Toluene (108-88-3) [2.5-10%] CERCLA, CSWHS, EPCRAWPC, GADSL, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, PROP65, SARA313, TOXICPOL, TOXICRCRA, TSCA, TXAIR, TXHWL

WARNING

This product can expose you to chemicals including Dichloromethane (Methylene chloride), which is known to the State of California to cause cancer, and Methanol, and Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory CODE Descriptions

- RQ = Reportable Quantity
- CERCLA = Superfund clean up substance
- GADSL = Global Automotive Declarable Substance List (GADSL)
- HAP = Hazardous Air Pollutants
- MASS = MA Massachusetts Hazardous Substances List
- NJHS = NJ Right-to-Know Hazardous Substances
- NRC = Nationally Recognized Carcinogens
- OSHA = OSHA Workplace Air Contaminants
- PA = PA Right-To-Know List of Hazardous Substances
- PRIPOL = Clean Water Act Priority Pollutants
- PROP65 = CA Prop 65
- SARA313 = SARA 313 Title III Toxic Chemicals
- TOXICPOL = Clean Water Act Toxic Pollutants
- TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
- TSCA = Toxic Substances Control Act
- TXAIR = TX Air Contaminants with Health Effects Screening Level
- TXHWL = TX Hazardous Waste List
- CSWHS = Clean Water Act Hazardous substances
- EPCRAWPC = EPCRA Water Priority Chemicals

16	OTHER INFORMATION
-----------	--------------------------

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

N/A = Not available N/D = Not determined

Revision Date: 1/23/2018